

PF	Product Fiche according to (EU) No 65/2014			
S	Supplier's name or trade mark	ALLENZI		
M	Model identifier	OLIMPIA 60 SS		
	Annual Energy Consumption	AEC hood	62.7	kWh/a
	Energy Efficiency Class	EEI class	D	
	Fluid Dynamic Efficiency	FDE hood	8.1	%
	Fluid Dynamic Efficiency class	FDE class	E	
	Light Efficiency	LE hood	14.0	lux/W
	Lighting Efficiency Class	LE class	D	
	Grease Filtering Efficiency	GFE hood	78.7	%
	Grease Filtering Efficiency class	GFE class	C	
	Minimum Air Flow in normal use	Q min	199.3	m³/h
	Maximum Air Flow in normal use	Q max	381.7	m³/h
	Air Flow at intensive/boost setting	Q boost	/	m³/h
	A-weighted Sound Power Emission at minimum speed	SPE min	49	dB(A) re 1pW
	A-weighted Sound Power Emission at maximum speed	SPE max	61	dB(A) re 1pW
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	/	dB(A) re 1pW
	Power consumption off mode	Po	0.00	W
	Power consumption in standby mode	Ps	0.00	W

Additional Information according to (EU) No 66/2014				
	Time increase factor	f	1.7	
	Energy Efficiency Index	EEI hood	89.3	%
	Measured air flow rate at best efficiency point	Q bep	199.6	m³/h
	Measured air pressure at best efficiency point	P bep	136	Pa
	Maximum air flow	Q max	381.7	m³/h
	Measured electric power input at best efficiency point	W bep	93.1	W
	Nominal power of the lighting system	WL	6.8	W
	Average illumination of the lighting system on the cooking surface	E middle	92	lux